


ACOUSTIC
FABRIC



M1.LAZIO VELVET-B
M1.LAZIO



0029



00C9



00G1



0081



0046



0024



0069



00E2



0016



00H1



0036



0026



00V5



00V3



0076



0093



0018



0021



M1.LAZIO VELVET-B M1.LAZIO

GENERAL FABRIC INFORMATION					
Quality Name	M1.LAZIO VELVET-B	Design Name	M1.LAZIO		
End-Use	CONTRACT - INHERENT FR	Width (±2cm)	142 cm (56")	Weight	440 gr/m ²
Composition	%100 PES	Specials			

PHYSICAL TESTS				
Test	Standarts		Results	
Abrasion End	EN ISO 12947-2		80000	
Wyzenbeek	ASTM D4157		200000	
Martindale-Pilling 2.000 Cycle	EN ISO 12945-2		4/5	
Brush Pilling	D3511-99A			
Test	Standarts		Warp	Weft
Seam Slippage	EN ISO 13936-2		2	2
Tear Strength	EN ISO 13937-3		40	40
Tensile Strength	EN ISO 13934-1		810	620
Colour Fastness Rubbing	EN ISO 105-X12(Dry/Wet)		4/5	4/5
Colour Fastness Light	EN ISO 105-B04			

FLAMMABILITY TESTS		
Test	Standarts	Results
Cigarette Test	BS 5852 PART 1 SOURCE 0	PASS
Match Testi	BS 5852 PART 1 SOURCE 1	PASS
Cigarette Test	EN 1021-1	PASS
Match Testi	EN 1021-2	PASS
Cigarette-Match Test	IMO PART 8	PASS
Cigarette-Match Test	BS 7176 LOW HAZARD	PASS
Cigarette Test	CALL 117	PASS
Cigarette Test	NFPA 260	PASS
M Testi	NF P 92 5XX (M1)	M1
B Testi	DIN 4102	B2

REPELLENCY / CLEANABILITY TESTS		
Test	Standarts	Results
Bleach Cleanable Test	AATCC 101-ACT TM1 With Extra Process	PASS

CARE CODES			
Washable	Wash 30°C gentle cycle	Care symbols	
Iron	Low iron at max 110°C		
Tumble dry	Do not tumble dry		
Bleach	Do not bleach		
Dry clean P	Dry-cleaning in perchloroethylene gentle cycle		

Our products fulfil the requirements of Annex XVII of REACH (incl. the use of azo-dyes, heavy metals, etc.) as well as the American requirement regarding total content of lead in children's articles)
 In stain repellent products, we always use human and environmental friendly C6 fluorocarbons. In FR treatment, we always use DecaBDE free FR compounds.
 The colours in production might slightly vary from this reference due to different lots in production.



SUSTAINABLE TEXTILES