



PL-M2E1




PL- M7M7




PL- FZ44




PL- Y5Y5




PL- 2536




PL- 25X3




PL- 29V4




PL- J2S1




PL- BNZ8




PL- 13K2




PL- D8D8




PL- D8E4




PL- N184




PL- T584




PL- U1B7




PL- 33A1




PL- 53A3




PL- J5N1



PL- T5D8




PL- K9K9



PL- J5B2




PL- G2L4



PL- 0025




PL- N8N8




PL- H2H2




PL- G284




PL- 29L4




PL- F1F1




PL- ENAD




PL- E1E1



PL- HEFZ



PL- F7F7



PL- FSFS

GENERAL FABRIC INFORMATION					
Quality Name	PLATIN-A	Design Name	PLATIN 01		
End-Use		Width (±2cm)	140 cm (55")	Weight	285 gr/mt²
Composition	%100 PES	Specials			

PHYSICAL TESTS				
Test	Standarts		Results	
Abrasion End	EN ISO 12947-2		35000	
Wyzenbeek	ASTM D4157			
Martindale-Pilling 2.000 Cycle	EN ISO 12945-2		4/5	
Brush Pilling	D3511-99A			
Test	Standarts		Warp	Weft
Seam Slippage	EN ISO 13936-2		3	3.5
Tear Strength	EN ISO 13937-3		71	152
Tensile Strength	EN ISO 13934-1		795	1358
Colour Fastness Rubbing	EN ISO 105-X12(Dry/Wet)		4	3/4
Colour Fastness Light	EN ISO 105-B04			

FLAMMABILITY TESTS		
Test	Standarts	Results
Cigarette Test	BS 5852 PART 1 SOURCE 0	PASS
Match Testi	BS 5852 PART 1 SOURCE 1 WITH TREA	PASS
Cigarette Test	EN 1021-1	PASS
Match Testi	EN 1021-2 WITH TREATMENT	PASS
Cigarette-Match Test	IMO PART 8 WITH TREATMENT	PASS
Cigarette-Match Test	BS 7176 LOW HAZARD WITH TREATME	PASS
Cigarette Test	CALL 117	PASS
Cigarette Test	NFPA 260	PASS

REPELLENCY / CLEANABILITY TESTS		
Test	Standarts	Results
Bleach Cleanable Test	AATCC 101-ACT TM1 With Extra Process	PASS

CARE CODES			
Washable	Wash 30°C gentle cycle	Care symbols	    
Iron	Low iron at max 110°C		
Tumble dry	Do not tumble dry		
Bleach	Do not bleach		
Dry clean P	Dry-cleaning in perchloroethylene gentle cycle		

Our products fulfil the requirements of Annex XVII of REACH (incl. the use of azo-dyes, heavy metals, etc.) as well as the American requirement regarding total content of lead in children's articles)
In stain repellent products, we always use human and environmental friendly C6 fluorocarbons. In FR treatment, we always use DecaBDE free FR compounds.
The colours in production might slightly vary from this reference due to different lots in production.



SUSTAINABLE TEXTILES